PATENT COOPERATION TREATY



Control of the Contro	
REC'D 11 AUG 2009	l
WIPO POT	

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference	FOR FURTHER ACT	ION See Form F	PCT/IPEA/416		
118656					
International application No.	International filing date	(day/month/year)	Priority date (day/month/year)		
PCT/SE2004/001349	20.09.2004		22.09.2003		
International Patent Classification (IPC) of	r national classification an	d IPC			
B65G 17/20, B65G 47/6	4				
Applicant		····			
Eton Systems AB et al		<u> </u>			
This report is the international pre- Authority under Article 35 and transport			is International Preliminary Examining 36.		
2. This REPORT consists of a total of	of 3 sheets	, including this cover	r sheet.		
3. This report is also accompanied b	y ANNEXES, comprising				
5-7					
(com to the applicant			sheets, as follows:		
and/or sheets			be been amended and are the basis of this report thority (see Rule 70.16 and Section 607 of the		
sheets which	supersede earlier sheets, b	ut which this Author	ity considers contain an amendment that goes		
beyond the di		al application as filed	d, as indicated in item 4 of Box No. I and the		
l —					
b. (sent to the Internation			number of electronic carrier(s))		
readable form only a			and/or tables related thereto, in computer o Sequence Listing (see Section 802 of the		
Administrative Instru		entail Box Rotating t	o sequence Listing (see section 602 of the		
4. This report contains indications re	elating to the following ite	ms:			
	f the report				
Box No. II Priority	•	•	·		
Box No. III Non-es	tablishment of opinion wit	h regard to novelty, i	inventive step and industrial applicability		
Box No. IV Lack of	funity of invention				
	documents cited	ations supporting sa	on succession.		
Box No. VII Certain	defects in the international	l application			
<u> </u>	observations on the intern				
Date of submission of the demand		Date of completion	of this report		
22.04.2005		27.07.2005			
Name and mailing address of the IPEA/S	E	Authorized officer			
Patent- och registreringsverket Box 5055					
S-102 42 STOCKHOLM		Ann Börjeson / MRo			
Feetimile No. +46 9 667 72 99		Talant No. 144	. 0 702 05 00		

BEST AVAILABLE COPY

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2004/001349

Box	No. I	Bas	sis of the report				
1.	With rotherw	egard to ise indic	o the language, this report is based on the international application in the language cated under this item.	e in which it was filed, unless			
		This rep	port is based on a translation from the original language into the following language s the language of a translation furnished for the purposes of:	· · · · · · · · · · · · · · · · · · ·			
		П	international search (under Rules 12.3 and 23.1(b))				
			publication of the international application (under Rule 12.4)				
			international preliminary examination (under Rules 55.2 and/or 55.3)				
2.	furnish	With regard to the elements of the international application, this report is based on (replacement sheets which have been turnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report):					
	닕		ernational application as originally filed/furnished				
	\boxtimes		scription:				
				as originally filed/furnished			
		pages* pages*					
		the clai					
		pages*		as originally filed/furnished y statement) under Article 19			
			* 13-15 received by this Authority on 24.0	•			
		pages*					
	\boxtimes	the dra					
			· ·	as originally filed/furnished			
		pages*		_			
		pages*					
		a seque	ence listing and/or any related table(s) - see Supplemental Box Relating to Sequence	Listing.			
3.		The an	nendments have resulted in the cancellation of:				
			the description, pages				
			the claims, Nos.				
			the drawings, sheets/figs				
		同	the sequence listing (specify):				
		同	any table(s) related to the sequence listing (specify):				
4.			eport has been established as if (some of) the amendments annexed to this report since they have been considered to go beyond the disclosure as filed, as indicated ()).				
			the description, pages				
		Ħ	the claims, Nos.				
		Ħ	the drawings, sheets/figs				
		Ħ					
		H	the sequence listing (specify): any table(s) related to the sequence listing (specify):				
*	If item	4 applie	es, some or all of those sheets may be marked "superseded."				

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2004/001349

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Claims Claims	1-10	YES NO
Inventive step (IS)	Claims Claims	1-10	YES NO
Industrial applicability (IA)	Claims Claims	_1-10	YES

2. Citations and explanations (Rule 70.7)

Reference is made to the following documents:

D1: US4936222 D2: US3759190

Document D1, which is considered to represent the most relevant state of the art, discloses a product carrier movable along a conveyor track from which the subject-matter of claims 1-10 differs in that the carrier arms are both pivotally suspended from each wheel unit and also pivotally supported in a holder. The carrier also contains a positioning mechanism to maintain a controlled distance between the wheel units. The two arms of the product carrier in D1 are rigidly connected to each other, involving that, if the conveyor is inclined, then the carrier and the carried objects will also be inclined.

Document D2 does not disclose anything about pivotability between carrier arms and the wheel units. Thus, it must be assumed that a rigid connection is present.

By means of the product carrier according to the invention, it is possible to maintain a controlled distance between the wheel units without having a direct and rigid connection between the wheel units, simultaneously allowing the carrier arms and the holder with carried products to hang down substantially vertically, independently of the inclination of the holder.

Thus, the invention defined in claims 1-10 is not previously known and it is not considered obvious to a person skilled in the art. Accordingly, it is novel and considered to involve an inventive step. The invention is industrially applicable.

24 -05- 2005

13

CLAIMS

- 1. A product carrier, moveable along a conveyor track (33, 34) in a conveyor arrangement, and designed as a trolley, which has at least two wheel units (3, 4) which are designed to be moved along the conveyor track, and a carrier arm (5, 6) which is <u>pivotally</u> suspended from each wheel unit and which is provided with carrier members (7, 8) for the products that are to be conveyed, said carrier arms (5, 6) being connected to one another by means of a positioning mechanism (9/45, 50, 51), **characterized in that** the carrier arms (5,6) are pivotally supported in a holder (10) in which the positioning mechanism is arranged and that said positioning mechanism maintains a selected essential distance (a) between the wheel units (3,4) regardless of the inclination of the track.
- 2. The product carrier as claimed in claim 1, **characterized in that** the positioning mechanism (9/45, 50, 51) comprises a parallel guide mechanism which essentially keeps the carrier arms (5, 6) parallel to one another, regardless of the inclination of the track, so that said distance (a) in relation to one another is largely maintained.
- 3. The product carrier as claimed in claim 1, **characterized in that** the positioning mechanism (9) comprises a toothed gearing having a number of gearwheels (19, 20, 21), which are rotatably supported in the holder (10).
- 4. The product carrier as claimed in claim 2 and 3, characterized in that the holder (10) is designed as a box in which the gearwheels (19, 20, 21) are rotatably supported and that the gearwheels comprise two outer gearwheels (19, 20) which are designed to follow the swiveling movements of the carrier arms (5), and an intermediate gearwheel (21) which intermeshes with the outer gearwheels, the two outer gearwheels having the same diameter.

- 5. The product carrier as claimed in claim 2, **characterized in that** the parallel guide mechanism (45, 50, 51) has parallel arms (45, 50, 51), which are directly or indirectly articulated in the carrier arms (5, 6) at a uniform distance.
- 6. The product carrier as claimed in claim 1, **characterized in that** the wheel units (4, 5) can be turned about their axes of rotation (17, 18) for adjustment to curved sections of the conveyor track (33, 34).
- 7. The product carrier as claimed in claim 6, **characterized in that** the distance (a) between the wheel units (5, 6) is variable within narrow limits.
- 8. The product carrier as claimed in claim 7, **characterized in that** the turning of the wheel units (3, 4) is achieved by torsion of the carrier arms (5, 6) about their longitudinal axis.
- 9. A conveyor arrangement comprising a first conveyor (33) and at least a second conveyor (34) together with a number of product carriers (1) designed as trolleys which are moveable along the conveyors for moving products, the first conveyor comprising a continuous track, and the trolleys having wheel units (3, 4) designed to run along the track, and the second conveyor comprising a chain conveyor in the form of a loop of links (36, 37) designed with members for receiving and holding the transported trolleys, said holding members being situated at a selected spacing interval (b) from one another, characterized in that the wheel units (3, 4) have pivotally suspended carrier arms (5, 6), which are connected to one another by means of a positioning mechanism (9/45, 50, 51) for maintaining a selected positional relationship between the wheel units, so that the wheel units essentially maintain an axial distance (a) from one another which largely corresponds to said spacing interval (b), and that the carrier arms are pivotally supported in a holder (10). in which said positioning mechanism is arranged.

AMENDED SHEET

2 4 -05- 2005

10. The conveyor arrangement as claimed in claim 9, **characterized in that** the reciprocal axial distance (a) is variable within narrow limits for adjustment to changes in the spacing interval (b) of the second conveyor (34).